

# Cash-Flo® Reduced Pressure Zone Backflow Preventer Type RPZ (bronze)

## DESCRIPTION

A Cash-Flo RPZ device (reduced pressure backflow preventer) provides maximum protection against back-pressure and back-siphonage. The RPZ consists of two independently acting check valves and a relief valve. The RPZ and ball valves are constructed from bronze and corrosion resistant internal components. The Cash-Flo RPZ is designed to streamline the number of working parts, making maintenance easy. The unique top-entry cover allows quick access to both check valves and relief valve. These Cash-Flo reduced pressure backflow preventers are available in 1/2" thru 2" sizes. The RPZ is designed for maximum system pressures to 175 psi. The maximum operating temperature is 180°F (82°C).

## FEATURES AND BENEFITS

Top-entry, single access cover:

*Provides easy access and servicing for valve internals.*

Short lay length:

*Ideal for installation in small spaces.*

Distinct, unique check assemblies:

*Eliminates installing checks in wrong positions.*

Internals composed of corrosion resistant materials:

*Longer life for the valve.*

Each repair kit includes seat rings:

*Provides for easy, inexpensive service and reduces parts inventory.*

Body, test cocks, and shut-off valves composed of bronze:

*Meets existing lead leaching standards.*

Meets all specifications of ASSE, AWWA and all other national approvals:



*Inspector friendly peace of mind!*

## SPECIFICATION

Reduced Pressure Zone Backflow Preventer shall protect against backflow by either back-pressure or back-siphonage from a cross-connection between potable water systems and substances that are high health hazards.


The device shall be constructed from bronze. It shall consist of two (2) mechanically independent, spring loaded, center stem guided check valves. It shall also have a hydraulically dependent differential pressure relief valve with the sensing passage set in an integral cast bronze body, with a single access cover. The assembly shall have four (4) vertical test cocks and two (2) shut-off valves which are quarter-turn, full-port, resilient seated and ball type.

The relief valve shall have removable stainless steel seat ring. The check valves shall be held into place by stainless steel clips and the check valve assemblies shall be non-interchangeable with silicone discs.




# Cash-Flo® Reduced Pressure Zone Backflow Preventer Type RPZ (bronze)

## TYPICAL INSTALLATION



## SPECIFICATION DATA



Type	Size	Part #	A	B	C	D	Width	Wgt with GV	Wgt less GV
			Inch	Inch	Inch	Inch			
RPZ II	1/2	CB9339E	9-1/4	5-1/2	5-21/32	3-5/8	3-5/32	4.5	3.25
RPZ II	3/4	CB9300E	9-3/4	5-1/2	5-21/32	3-5/8	3-5/32	5	3.25
RPZ	1	CB9201E	13	8	6-1/8	3-3/4	4	9.5	7
RPZ	1-1/4	CB9202E	14-3/8	9	7-1/4	4-1/8	4-9/16	13	8.5
RPZ	1-1/2	CB9203E	17	10-1/2	5-1/2	8	5-1/8	18.5	12
RPZ	2	CB9204E	20	12-1/2	9	5	5-3/4	32	21

### Performance:

Max. working pressure . . . . . 175 psi

Max. working temperature . . . . 180°F (82°C)

Hydrostatic Test Pressure. . . . . 350 psi

### Materials:

Valve Body . . . . . Bronze

Access Cover . . . . . Bronze

Polymers . . . . . Noryl™, NSF listed

Elastomers . . . . . Silicon



Springs . . . . . Stainless steel

## CONNECTIONS

1/2", 3/4", 1", 1-1/4, 1-1/2" and 2"

## CERTIFICATIONS

The Cash-Flo® Reduced Pressure Zone Backflow Preventer Type RPZ (bronze) and RPZ II (bronze) are CSA and ASSE 1013 listed, AWWA Compliant C511. All major national approvals.



### RATED FLOW

(Established by Approval Agencies)

Pipe size	Capacity thru Schedule 40 Pipe (GPM)			
	5 ft/sec	7.5 ft/sec	10 ft/sec	15 ft/sec
3/4"	8	12	17	25
1"	13	20	27	40
1-1/4"	23	35	47	70
1-1/2"	32	48	63	95
2"	52	78	98	157